

SUPRA 4.0 XLITE

TECHNICAL DATA SHEET - FLEBI SUPRA 4.0 XLITE



COMPONENTS

BATTERY	36V / 7.8Ah lithium battery
FRAME	6061 Alloy, TIG welding, 16"x272mm, folding
ENGINE	Rear hub motor
FORK	16", Steel
CONTROL PANEL	LCD Panel
ELECTRONIC CONTROL	36V, limited to 25km/h
RIMS	16"x1.75" single wall alloy, 28/36H, black / CNC
PEDAL SENSOR	Left side, dual hall, 12 signals
CHARGER	36V, EU SS connector. 36V, EU SS connector
TYRES	16"x1.75 KENDA
FRONT BRAKE	V-brake
REAR BRAKE	V-brake
FRONT LIGHT	6V WUXING
REAR LIGHT	Rear reflector
CHAINWHEEL	KMC, brown (Chainring: 52T x 165mm steel)
BRAKE LEVERS	Tektro with brake sensor
PEDALS	PP / Alloy, 9/16", folding with bearings and reflector
GEARS	Single speed
HANDLES	Black TPR
REAR DERAILLEUR LEVERS	N/A
HANDLEBARS	Alloy, 22.2x580mm, low rise, with alloy folding stem, sand black
SADDLE	Vinyl cover, black
STEM	Optional
RACK	Black solid alloy tube, includes PU transport wheels.
BELL	Included

SPECIFICATIONS

WEIGHT (KG)	16
DIMENSIONS (CM)	130x106x57
FOLDING TIME (S)	10
FOLDED DIMENSIONS (CM)	62x33x65
HANDLEBAR HEIGHT (CM)	106(max)
SADDLE HEIGHT (CM)	110(max)
MAX LOAD (KG)	110
MAX HEIGHT (M)	1.85
RANGE(KM)	up to 50km
RECHARGING TIME (H)	4
VOLTAGE (V)	100-240 VAC
MAX SPEED (KM/H)	25
BATTERY LIFE (CYCLES)	800
MAXIMUM SLOPE (%)	15%
TYRE PRESSURE	3.1 bar 45 PSI
CERTIFICATION	CE, EN15194 – bicycles EPAC
PACKAGE DIMENSIONS (CM)	95x73x28cm